

TECHNICAL DATA SHEET



FULL SYNTHETIC MARINE 2-CYCLE OIL

PRODUCT # 11149

TEST

ASTM

TYPICAL

| | | |
|--------------------------------|---------------|---------------------|
| Specific Gravity @ 60°F | D-1298 | .844 |
| API @ 600°F | D-1298 | 36.1 |
| Viscosity @ 100°C | D-445 | 7.5 minimum |
| Flash Point, COC °F | D-92 | 175 |
| LBS/GAL @ 60°F | D-1298 | 7.02 |
| Sulfated Ash, wt% | | 0.25 maximum |
| Nitrogen wt% | | 0.050 |
| Color | | Blue/Green |
| Pour Point, °C (°F) | D-97 | -51 (-60) |

Lucas Synthetic Marine 2-Cycle Oil is blended from both PAO (Group IV) and Group III synthetic base oils and combines these with a low-ash detergent inhibitor additive package that balances the need to minimize spark plug fouling, pre-ignition and clean combustion chambers with high levels of lubrication to discourage ring sticking and extend engine life. **Lucas Synthetic Marine 2-Cycle Oil** is a very low-smoke formula and blends effortlessly with fuel. It is formulated to meet or exceed ISO EGD, JASO FD and API TC.

This product is suitable for both pre-mix and oil injection systems. **Lucas Synthetic Marine 2-Cycle Oil** is a premium 2-Stroke lubricant suitable for both outboards and personal watercraft.