

TECHNICAL DATA SHEET



SYNTHETIC SAE 5W-20 MOTORCYCLE OIL

PRODUCT # 10704, 10735, 10737

TEST

ASTM

TYPICAL

API Gravity	D-1298	33.8
Specific Gravity @ 60°F	D-1298	.8560
Density @ 60°F LBS/US Gal	D-1298	7.128
Viscosity @ 40°C, cSt	D-445	49
Viscosity @ 100°C, cSt	D-445	8
Viscosity Index	D-2270	134
Color		Light Brown
Flash Point, COC °F	D-92	455

Lucas Synthetic SAE 5W-20 High Performance Motorcycle Oil is formulated with an exclusive additive package that is not found in other brands. It contains a high level of detergents and dispersants to resist sludge and varnish formation.

Lucas Synthetic SAE 5W-20 High Performance Motorcycle Oil is formulated to lower engine temperature and raise oil pressure, reduce noise and increase performance. It offers maximum protection with minimum drag.

The exclusive additive package in Lucas Synthetic SAE 5W-20 High Performance Motorcycle Oil allows for extended drain intervals.

Lucas Synthetic SAE 5W-20 High Performance Motorcycle Oil far exceeds all OEM specifications.

Formulated to meet ALL motorcycles that call for a Synthetic SAE 5W-20 motor oil.

Meets or exceeds: API SM, SL, SJ, SH, SG, SF, CC, CD • JASO MA/MA-2 • ACEA A3