

## TECHNICAL DATA SHEET

# ENGINE ASSEMBLY GREASE

## NLGI #2

PRODUCT # 10891

### TEST

### ASTM

### TYPICAL

<b>Color</b>	<b>Visual</b>	<b>Blue</b>
<b>Texture</b>	<b>Visual</b>	<b>Smooth</b>
<b>Penetration Worked 60 Strokes</b>	<b>D-217</b>	<b>265-295</b>
<b>Dropping Point, D-2265 °F (°C) min</b>	<b>D-2265</b>	<b>572 (300)</b>
<b>4 Ball Wear, Scar Diameter, mm</b>	<b>D-2266</b>	<b>0.40</b>
<b>4 Ball EP, Weld Point, Kg</b>	<b>D-2596</b>	<b>500</b>
<b>Base Oil Viscosities</b>		
<b>cSt @ 40°C</b>	<b>D-445</b>	<b>100 min</b>
<b>cSt @ 100°C</b>	<b>D-445</b>	<b>17</b>
<b>Viscosity Index</b>	<b>D-2270</b>	<b>95</b>

**Lucas Engine Assembly Grease is a heavy duty and corrosion resistant grease made of Calcium Sulfonate Complex thickener. It is suitable for all metals. It provides anti-wear, extreme pressure properties and dissolves completely in oil. Provides protection during initial start-up and is designed for use on cams and lifters. It is also recommended for use on distributor caps, rocker shafts, rocker tips, pushrod tips, wrist pins and valve guides. Tested and approved by top NASCAR teams.**