

## TECHNICAL DATA SHEET



# HIGH PERFORMANCE SYNTHETIC FORK OIL LIGHT (5 wt.)

PRODUCT # 10771

### TEST

### ASTM

### TYPICAL

<b>Specific Gravity @ 60°F</b>	<b>D-1298</b>	<b>0.844</b>
<b>Density @ 60°F LBS/US Gal</b>	<b>D-1298</b>	<b>7.03</b>
<b>Flash Point, COC °F</b>	<b>D-92</b>	<b>428</b>
<b>Viscosity @ 40°C cSt</b>	<b>D-445</b>	<b>25.34</b>
<b>Viscosity @ 100°C cSt</b>	<b>D-445</b>	<b>5.5</b>
<b>Viscosity Index</b>	<b>D-2270</b>	<b>148</b>
<b>Color</b>	<b>Visual</b>	<b>Blue Green</b>

**Lucas High Performance Synthetic Fork Oil Light (5 wt.) is formulated with the highest quality synthetic base oils and our unique additive system to improve performance and extend the life of your fork's internal parts. Provides highly responsive handling and better shock behavior.**

**Our High Performance Synthetic Fork Oil Light (5 wt.) prevents seal hardening, oxidation and oil thickening, foaming and static friction. Also, reduces thermal expansion and provides better wear protection. Designed for use in all systems, including damping rod, cartridge, bladder, conventional and inverted forks.**

**16 oz (473 mL) bottle**