

Z MASTER®

4000 SERIES

SEE PAGE 2 FOR BATTERY
REVOLUTION SERIES OPTIONS



HORIZON360
CONTRACTOR BUSINESS SOFTWARE

COMPATIBLE

BUILT TO DOMINATE. READY TO REIGN.

Show up big, bad, and fearless. The Z Master 4000 is the durability king, providing a royal ride with MyRIDE® suspension system and grass-kicking TURBO FORCE® deck with a bold, dominating look. It's going to cut a path that you know will be noticed.

PRIDE CUT IN EVERY PASS

Constructed with high-strength materials and engineered with proven technologies, the TURBO FORCE cutting deck is built from 100 years of experience and over 100 million unrelenting hours of real-world results.

A BEAST FOR BEAUTY

Every Z Master 4000 is loaded with a heavy-duty front-end design, TURBO FORCE deck with bullnose bumper, and pro-grade engine transforming a battlefield of brutal vegetation into a pristine pro cut.

GET COMFORTABLE CRUSHING IT

Keep mowing full blast in full-time comfort with a deluxe suspension seat. Or get battle-ready with the MyRIDE® Suspension System.



NOW AVAILABLE

Triple/
DFS bagger
for HDX PRO XL
models

PERFECT ONE-PASS CUTTING

The TURBO FORCE® Cutting Deck: enhances the after-cut appearance through dual capture anti-scalp rollers, rubber discharge chute, a clear sight-line to rear tires and the offset 7-gauge steel deck.

4.4–6.6 Maximum Acres/Hour

Maximum acres per hour based on 90% efficiency
(MPH x width of cut). Actual productivity dependent upon conditions.



NO MESSING AROUND

Pairing the durable rugged I-beam front end, along with the TURBO FORCE deck's bullnose bumper and heavy-duty cast aluminum spindle housings, durability is king.



MyRIDE® SUSPENSION SYSTEM

Take it to the next level of comfort with the industry's only adjust-on-the-fly rear suspension with beefy shocks featuring up to 3 inches of travel to soak up what Mother Nature puts in your path.



MOW ON AND ON

4000s come with conveniences like the optional electronic deck lift assist, to front step thru deck, and USB ports.

	HD		HDX MyRIDE [®] SUSPENSION SYSTEM			PRO				HDX PRO																
	74050	74054	74052 HDX	74055 HDX	74057 HDX	74000	74002	74004	74035	74010 HDX Pro	74015 HDX Pro	74020 HDX Pro XL	74022 HDX Pro XL	74024 HDX Pro XL												
POWER SYSTEM															NEW											
Commercial Engines at 3600 RPM*	25.5 Kawasaki FX801V (852cc)		▶ 31 hp Kawasaki FX921V (999cc)		▶ 35 hp Kawasaki FX1000V (999cc)	24.5 Kawasaki FX751 (852cc)	▶ 25.5 Kawasaki FX801V (852cc)		▶ 26.5 hp Kohler Command Pro EFI (747cc)	▶ 31 hp Kawasaki FX921V (999cc)		▶ 35 hp Kawasaki FX1000 (999cc)														
Starter	Electric		Electric			Electric				Electric																
Heavy-Duty Canister Air Cleaner	Standard		Standard			Standard				Standard																
Drive Tires	Voodoo Trac 26" x 10.5" - 12" (66 x 26.7 - 30.5 cm)	▶ Voodoo Trac 26" x 12" - 12" (66 x 30.5 - 30.5 cm)	Voodoo Trac 26" x 10.5" - 12" (66 x 26.7 - 30.5 cm)	▶ Voodoo Trac 26" x 12" - 12" (66 x 30.5 - 30.5 cm)		24" x 9.5" - 12" (61 x 24.1 - 30.5 cm)	24" x 10.5" - 12" (61 x 26.7 - 30.5 cm)	24" x 12" - 12" (61 x 30.5 - 30.5 cm)		24" x 10.5" - 12" (61 x 26.7 - 30.5 cm)	▶ 24" x 12" - 12" (61 x 30.5 - 30.5 cm)	▶ Super Turf 26" x 12" - 12" (66 x 30.5 - 30.5 cm)		▶ Voodoo Trac 26" x 12" - 12" (66 x 30.5 - 30.5 cm)												
Caster Tires	15" x 6.5" - 6" Pneumatic (38 x 16.5 - 15.2 cm)		15" x 6.5" - 6" Pneumatic (38 x 16.5 - 15.2 cm)			13" x 6.5" - 6" Flat-Free Semi-Pneumatic (33 x 16.5 - 15.2 cm)				13" x 6.5" - 6" Flat-Free Semi-Pneumatic (33 x 16.5 - 15.2 cm)		▶ 15" x 6.5" - 6" Flat-Free Semi-Pneumatic (38.1 x 16.5 - 15.2 cm)														
Fuel/Capacity	Gas/10-Gal (37.9 L)		Gas/10-Gal (37.9 L)			Gas/10-Gal (37.9 L)				Gas/10-Gal (37.9 L)																
Digital Hour Meter	Standard		Standard			Standard				Standard																
Hydraulic Drive System	ZT-4400 Integrated Pumps & Wheel Motors		ZT-4400 Integrated Pumps & Wheel Motors			ZT-4400 Integrated Pumps & Wheel Motors				▶ ZT-5400 Integrated Pumps & Wheel Motors																
Maximum Forward Speed	12 mph (19.3 km/h)		12 mph (19.3 km/h)			10 mph (16.1 km/h)				▶ 12 mph (19.3 km/h)																
Clutch	Electromagnetic		Electromagnetic			Electromagnetic				Electromagnetic																
MOWING DECKS																										
Deck Size	52" (132.1 cm)	▶ 60" (152.4 cm)	52" (132.1 cm)	▶ 60" (152.4 cm)	▶ 60" (152.4 cm)	48" (121.9 cm)	▶ 52" (132.1 cm)	▶ 60" (152.4 cm)	60" (152.4 cm)	52" (132.1 cm)	▶ 60" (152.4 cm)	60" (152.4 cm)	▶ 72" (182.9 cm)	▶ 72" (182.9 cm)												
Cutting Deck	7-Gauge TURBO FORCE		7-Gauge TURBO FORCE			7-Gauge TURBO FORCE				7-Gauge TURBO FORCE																
Deck Lift Design	Extension Spring		Extension Spring			Extension Spring				Extension Spring																
Spindle Housings	9" (22.9 cm) Dia. Aluminum		9" (22.9 cm) Dia. Aluminum			9" (22.9 cm) Dia. Aluminum				9" (22.9 cm) Dia. Aluminum																
1" (2.5 cm) Spindle Shaft	Standard		Standard			Standard				Standard																
Spindle Bearings	Maintenance-Free		Maintenance-Free			Maintenance-Free				Maintenance-Free																
Adjustable Height of Cut Foot Pedal	Standard, 1.5" - 5.5" in .25" increments (3.8 - 14 cm in .6 cm increments)		Standard, 1.5" - 5.5" in .25" increments (3.8 - 14 cm in .6 cm increments)			Standard, 1.5" - 5.5" in .25" increments (3.8 - 14 cm in .6 cm increments)				Standard, 1.5" - 5.0" in .25" increments (3.8 - 12.7 cm in .6 cm increments)																
Deck Depth	5.5" (14 cm)		5.5" (14 cm)			5.5" (14 cm)				5.5" (14 cm)																
Blades	.204" (.5 cm) Heat-Treated Steel		.204" (.5 cm) Heat-Treated Steel			.204" (.5 cm) Heat-Treated Steel				.204" (.5 cm) Heat-Treated Steel																
Blade Tip Speed	18,500+ ft/min		18,500+ ft/min			18,500+ ft/min				18,500+ ft/min																
Belt Construction	Aramid Fiber V-Belt		Aramid Fiber V-Belt			Aramid Fiber V-Belt				Aramid Fiber V-Belt																
FEATURES																										
MyRIDE [®] Suspension System			▶ MyRIDE Suspension System							▶ MyRIDE Suspension System																
Comfort Platform	N/A									N/A																
Platform Travel	N/A		3.0" (7.62 cm)							N/A																
Shocks	N/A		1 center / 2 rear							N/A																
Seat	N/A		High-Back Comfort							N/A																
Adjustability	N/A		5 Detents, Infinite Adjustability							N/A																
2" Hitch Receiver	Standard		Standard			Standard				Standard																
Steering Controls	1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened		1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened			1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened				1-5/8" (4.1 cm) Dia. Grips; Adjustable, Dampened																
Operator Seat	Deluxe Suspension with Armrests		Deluxe Comfort with Armrests			Deluxe Suspension with Armrests				Deluxe Suspension with Armrests																
LED Lights	Standard		Standard			Optional				Optional																
Step-Through Floorpan	Standard		N/A			▶ Standard				Standard																
Electric Deck Lift Assist	Optional		▶ Standard	Optional		Optional				Optional																
Smart Hour Meter & USB	Standard		Standard			Standard				Standard																
Warranty**	5-Year 1250-Hour 2-Year No Hour Limit		5-Year 1250-Hour 2-Year No Hour Limit			5-Year 1250-Hour 2-Year No Hour Limit				▶ 5-Year 1500-Hour 2-Year No Hour Limit																
WEIGHTS AND MEASUREMENTS																										
Weight	1,085 lbs.	492.1 kg	1,185 lbs.	537.5 kg	1,185 lbs.	537.5 kg	1,317 lbs.	597.4 kg	1,048 lbs.	475.4 kg	1,085 lbs.	492.1 kg	1,185 lbs.	537.5 kg	1,185 lbs.	537.5 kg	1,085 lbs.	492.1 kg	1,185 lbs.	537.5 kg	1,360 lbs.	616.9 kg	1,300 lbs.	589.7 kg	-	-
Deck Clearance Width	53.7"	136.4 cm	61.7"	156.7 cm	61.7"	156.7 cm	61.7"	156.7 cm	49.7"	126.2 cm	53.7"	136.4 cm	61.7"	156.7 cm	61.7"	156.7 cm	53.7"	136.4 cm	61.7"	156.7 cm	65.5"	166.4 cm	75.6"	192.0 cm	75.6"	192.0 cm
Deflector Width	67.6"	171.7 cm	75.7"	192.3 cm	75.7"	192.3 cm	75.7"	192.3 cm	63.6"	161.5 cm	67.6"	171.7 cm	75.7"	192.3 cm	75.7"	192.3 cm	67.6"	171.7 cm	75.7"	192.3 cm	75.3"	191.3 cm	87.6"	222.5 cm	87.6"	222.5 cm
Length	79.2"	201.2 cm	83.1"	211.1 cm	83.1"	211.1 cm	83.1"	211.1 cm	79.2"	201.2 cm	79.2"	201.2 cm	83.1"	211.1 cm	83.1"	211.1 cm	79.2"	201.2 cm	83.1"	211.1 cm	86.5"	219.7 cm	89.3"	226.8 cm	89.3"	226.8 cm

*The gross horsepower of these gasoline engines was laboratory rated at 3600 rpm by the engine manufacturer in accordance with SAE J1940 or SAE J1995. As configured to meet safety, emission and operating requirements, the actual engine horsepower on these mowers will be significantly lower. **See your local Toro dealer or consult owners manual for complete warranty details.